

# MATERIALS SAFETY DATA SHEET



## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : Bullet Roof GRP Roofing Topcoat

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Registered company name : Bullet Building Products Ltd Address :

Barbot Hall Industrial Estate, Mangham Road, Rotherham S61 4RJ

Telephone : 01274 752643

sales@bulletbp.co.uk

www.bulletbuildingproducts.co.uk

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Reproductive toxicity, Category 2 (Repr. 2, H361).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Specific target organ toxicity (repeated exposure), Category 1 (STOT RE 1, H372).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

### 2.2. Label elements

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS07



GHS08



GHS02

Signal Word :

DANGER

Product identifiers :

EC 202-851-5            STYRENE

Hazard statements :

H226                      Flammable liquid and vapour.  
H315                      Causes skin irritation.  
H319                      Causes serious eye irritation.  
H335                      May cause respiratory irritation.  
H361d                     Suspected of damaging the unborn child.  
H372                      Causes damage to organs through prolonged or repeated exposure (if inhaled).

Precautionary statements - Prevention :

P201                      Obtain special instructions before use.  
P202                      Do not handle until all safety precautions have been read and understood.  
P210                      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240                      Ground/bond container and receiving equipment.  
P241                      Use explosion-proof electrical/ventilating/lighting/.../equipment.  
P242                      Use only non-sparking tools.

P243                      Take precautionary measures against static discharge.  
P260                      Do not breathe dust/fume/gas/mist/vapours/spray.  
P264                      Wash ... thoroughly after handling.  
P270                      Do not eat, drink or smoke when using this product.  
P271                      Use only outdoors or in a well-ventilated area.  
P280                      Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P302 + P352             IF ON SKIN: Wash with plenty of water/...  
P303 + P361 + P353    IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340             IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338    IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
  
P308 + P313             IF exposed or concerned: Get medical advice/attention.  
P312                      Call a POISON CENTER/doctor/.../if you feel unwell.  
P314                      Get medical advice/attention if you feel unwell.  
P321                      Specific treatment (see ... on this label).  
P332 + P313             If skin irritation occurs: Get medical advice/attention.  
P337 + P313             If eye irritation persists: Get medical advice/attention.  
P362 + P364             Take off contaminated clothing and wash it before reuse.  
P370 + P378             In case of fire: Use... to extinguish.

Precautionary statements - Storage :

P403 + P233             Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235             Store in a well-ventilated place. Keep cool.  
P405                      Store locked up.

Precautionary statements - Disposal :

P501                      Dispose of contents/container to ...

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 471_34_1 CAS: 471-34-1 EC: 207-439-9  CALCIUM CARBONATE		[1]	10 <= x % < 25
INDEX: 601_026_00_0 CAS: 100-42-5 EC: 202-851-5  STYRENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Repr. 2, H361d STOT RE 1, H372 Aquatic Chronic 3, H412	[1]	10 <= x % < 25
INDEX: 13463_67_7 CAS: 13463-67-7 EC: 236-675-5  TITANIUM DIOXIDE		[1]	2.5 <= x % < 10

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

---

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)
- sulphur dioxide (SO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

---

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not inhale vapours.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

---

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

No data available.

#### Occupational exposure limits :

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
471-34-1	10 mg/m <sup>3</sup>	-	-	-	TI
100-42-5	100 ppm	250 ppm	-	-	-
13463-67-7	10 mg/m <sup>3</sup>	-	-	-	TI

### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides according with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- A3 (Brown)

---

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state : Paste.

#### Important health, safety and environmental information

pH : Not relevant.

Boiling point/boiling range : Not specified.

Flash Point : 32.00 °C.

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : > 1

Water solubility : Insoluble.

Viscosity : 35 000 - 45 000 cps

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

### 9.2. Other information

No data available.

---

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.

- heating

- heat

- flames and hot surfaces

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)
- sulphur dioxide (SO<sub>2</sub>)

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

Suspected human reproductive toxicant.

Suspected of damaging the unborn child.

Causes severe damage to organs in the event of repeated or prolonged exposure.

#### 11.1.1. Substances

##### Specific target organ systemic toxicity - repeated exposure :

STYRENE (CAS: 100-42-5)

Inhalation route (Vapours) :

$0,025 < C \leq 0,2$  mg/l/6hrs/day

Duration of exposure : 90 days

#### 11.1.2. Mixture

No toxicological data available for the mixture.

##### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 100-42-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

---

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

---

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

### 14.1. UN number

1325

### 14.2. UN proper shipping name

UN1325=FLAMMABLE SOLID, ORGANIC, N.O.S.  
(styrene)

### 14.3. Transport hazard class(es)

- Classification :



4.1

### 14.4. Packing group

III

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	III	4.1	40	5 kg	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	4.1	-	III	5 kg	F-A,S-G	223 274 915	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	4.1	-	III	446	25 kg	449	100 kg	A3	E1
	4.1	-	III	Y443	10 kg	-	-	A3	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

#### - Container information:

No data available.

#### - Particular provisions:

No data available.

### 15.2. Chemical safety assessment

No data available.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.