

# SAFETY DATA SHEET



## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name **BULLET ROOF MONO TOP**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Polyurea coating**

Identified Uses	Industrial	Professional	Consumer
Brush/roller/trowel/spray application	-	SU: 19. ERC: 10a, 11a, 8a, 8c, 8d, 8f. PROC: 10, 11, 15, 19, 9. PC: 1, 14, 15, 9a. LCS: PW.	-

### 1.3. Details of the supplier of the safety data sheet

Name **Bullet Building Products Ltd**  
Full address **Barbot Hall Industrial Estate, Mangham Road**  
District and Country **Rotherham. S61 4RJ**  
**01274 752643**  
  
Tel. **01274 752643**  
e-mail address of the competent person **sales@bulletbp.co.uk**  
responsible for the Safety Data Sheet

### 1.4. Emergency telephone number

For urgent inquiries refer to

**United Kingdom**  
**999/112 emergency**  
**111 non-emergency medical number**  
**NHS 111 (England)**  
**NHS 24 (Scotland)**  
**NHS Direct (Wales)**

**Ireland**  
**National Poisons Information Centre, Beaumont Hospital, PO Box 1297, Beaumont**  
**Road, Dublin 9**  
**018092166**  
**018092566**

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

## SECTION 2. Hazards identification ... / >>

Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.
--	------	--

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

<b>H225</b>	Highly flammable liquid and vapour.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH204</b>	Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P260</b>	Do not breathe dust / fume / gas / mist / vapours / spray.
<b>P331</b>	Do NOT induce vomiting.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P303+P361+P353</b>	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
<b>P280</b>	Wear protective gloves/ protective clothing / eye protection / face protection.

**Contains:** HYDROCARBONS, C9, AROMATICS  
POLYOXYPROPYLENEDIAMINE  
AROMATIC POLYISOCYANIC PREPOLYMER  
3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER,  
ISOCYANURATE TYPE  
ISOPHORONE DIISOCYANATE

**As from 24 August 2023 adequate training is required before industrial or professional use.**

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :

268,98

Limit value:

500,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.1. Substances

Information not relevant

## SECTION 3. Composition/information on ingredients ... / >>

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER, ISOCYANURATE TYPE</b>		
INDEX	$15 \leq x < 16,5$	STOT SE 3 H335, Skin Sens. 1B H317
EC	931-312-3	
CAS	53880-05-0	
REACH Reg.	01-2119488734-24	
<b>POLYOXYPROPYLENEDIAMINE</b>		
INDEX	$5 \leq x < 9$	Skin Corr. 1B H314, Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC	618-561-0	
CAS	9046-10-0	
REACH Reg.	01-2119557899-12	
<b>HYDROCARBONS, C9, AROMATICS</b>		
INDEX	$5 \leq x < 9$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066
EC	918-668-5	
CAS	128601-23-0	
REACH Reg.	01-2119455851-35	
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
INDEX	$4,5 \leq x < 5$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l
EC	215-535-7	
CAS	1330-20-7	
REACH Reg.	01-2119488216-32	
<b>BENZALDEHYDE</b>		
INDEX	$4,5 \leq x < 5$	Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412 LD50 Oral: 1430 mg/kg, LC50 Inhalation mists/powders: 3 mg/l/4h
EC	202-860-4	
CAS	100-52-7	
REACH Reg.	01-2119455540-44	
<b>AROMATIC POLYISOCYANIC PREPOLYMER</b>		
INDEX	$4 \leq x < 4,5$	Eye Irrit. 2 H319, Skin Sens. 1 H317
EC	609-378-7	
CAS	37273-56-6	
<b>TOLUENE</b>		
INDEX	$1 \leq x < 1,5$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC	203-625-9	
CAS	108-88-3	
REACH Reg.	01-2119471310-51	
<b>ISOBUTYL ACETATE</b>		
INDEX	$0,5 \leq x < 0,6$	Flam. Liq. 2 H225, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: C
EC	203-745-1	
CAS	110-19-0	
REACH Reg.	01-2119488971-22	
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		
INDEX	$0,2 \leq x < 0,25$	Flam. Liq. 3 H226, STOT SE 3 H336
EC	203-603-9	
CAS	108-65-6	
REACH Reg.	01-2119475791-29	
<b>QUARTZ</b>		
INDEX	$0,2 \leq x < 0,25$	STOT RE 1 H372
EC	238-878-4	
CAS	14808-60-7	
REACH Reg.	01-2120770509-45	
<b>ETHYL ACETATE</b>		
INDEX	$0,15 \leq x < 0,2$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC	205-500-4	
CAS	141-78-6	
REACH Reg.	01-2119475103-46	

## SECTION 3. Composition/information on ingredients ... / >>

### ISOPHORONE DIISOCYANATE

INDEX 615-008-00-5  $0,15 \leq x < 0,2$

EC 223-861-6

CAS 4098-71-9

REACH Reg. 01-2119490408-31

### PHOSPHORIC ACID

INDEX 015-011-00-6  $0 \leq x < 0,05$

EC 231-633-2

CAS 7664-38-2

REACH Reg. 01-2119485924-24

Acute Tox. 1 H330, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: 2 Skin Sens. 1 H317:  $\geq 0,5\%$ , Resp. Sens. 1 H334:  $\geq 0,5\%$   
LC50 Inhalation vapours: 0,04 mg/l/4h

Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B  
Skin Corr. 1B H314:  $\geq 25\%$ , Skin Irrit. 2 H315:  $\geq 10\%$ , Eye Dam. 1 H318:  $\geq 25\%$ , Eye Irrit. 2 H319:  $\geq 10\%$

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency

## SECTION 6. Accidental release measures ... / >>

procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičkim na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuovos higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające

**SECTION 8. Exposure controls/personal protection ... / >>**

		rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

**POLYOXYPROPYLENEDIAMINE**
**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,015	mg/l
Normal value in marine water	0,014	mg/l
Normal value for fresh water sediment	0,132	mg/kg
Normal value for marine water sediment	0,125	mg/kg
Normal value of STP microorganisms	7,5	mg/l
Normal value for the food chain (secondary poisoning)	6,93	mg/kg
Normal value for the terrestrial compartment	0,018	mg/kg
Normal value for the atmosphere	NPI	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					NPI	NPI	NPI	5,29 mg/m3
Skin					MED	MED	NPI	2,5 mg/kg bw/d

**HYDROCARBONS, C9, AROMATICS**
**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				7,5 mg/kg bw/d				
Inhalation				32 mg/m3				151 mg/m3
Skin				7,5 mg/kg bw/d				12,5 mg/kg bw/d







**SECTION 8. Exposure controls/personal protection ... / >>**

**ISOBUTYL ACETATE**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	300	62	600 (C)	124 (C)	
VLA	ESP	724	150			
VLEP	FRA	710	150	940	200	
TLV	GRC	950	200	950	200	
GVI/KGVI	HRV	241	50	723	150	
VLEP	ITA	241	50	723	150	
RD	LTU	241	50	723	150	
TGG	NLD	480				
VLE	PRT	241	50	723	150	
NDS/NDSCh	POL	240		720		
TLV	ROU	241	50	723	150	
NPEL	SVK	241	50	723	150	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	903	187	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,17	mg/l
Normal value in marine water	0,017	mg/l
Normal value for fresh water sediment	0,877	mg/kg
Normal value for marine water sediment	0,88	mg/kg
Normal value of STP microorganisms	200	mg/l
Normal value for the terrestrial compartment	0,0755	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					600 mg/m3	600 mg/m3	300 mg/m3	300 mg/m3
Skin						10 mg/kg bw/d		10 mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>**
**2-METHOXY-1-METHYLETHYL ACETATE**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
AGW	DEU	270	50	270	50	
MAK	DEU	270	50	270	50	
VLA	ESP	275	50	550	100	SKIN
VLEP	FRA	275	50	550	100	SKIN
HTP	FIN	270	50	550	100	SKIN
TLV	GRC	275	50	550	100	
GVI/KGVI	HRV	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
RD	LTU	250	50	400	75	SKIN
TGG	NLD	550				
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
NPEL	SVK	275	50	550	100	SKIN
MV	SVN	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,635	mg/l
Normal value in marine water	0,064	mg/l
Normal value for fresh water sediment	3,29	mg/kg
Normal value for marine water sediment	0,329	mg/kg
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	0,29	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					550 mg/m <sup>3</sup>			275 mg/m <sup>3</sup>
Skin								796 mg/kg bw/d

**QUARTZ**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
RD	LTU	0,1				
TGG	NLD	0,075				RESP
VLE	PRT	0,025				RESP
NDS/NDSch	POL	0,1				RESP
TLV	ROU	0,1				RESP
NPEL	SVK	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

**SECTION 8. Exposure controls/personal protection ... / >>**
**ETHYL ACETATE**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
VLA	ESP	734	200	1468	400	
VLEP	FRA	734	200	1468	400	
HTP	FIN	730	200	1470	400	
TLV	GRC	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
RD	LTU	500	150	1100 (C)	300 (C)	
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
NPEL	SVK	734	200	1468	400	
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,24	mg/l
Normal value in marine water	0,024	mg/l
Normal value for fresh water sediment	1,15	mg/kg
Normal value for marine water sediment	0,115	mg/kg
Normal value of STP microorganisms	650	mg/l
Normal value for the terrestrial compartment	0,148	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					1468 mg/m <sup>3</sup>	1468 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>
Skin								63 mg/kg bw/d

**SECTION 8. Exposure controls/personal protection ... / >>**
**ISOPHORONE DIISOCYANATE**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,046	0,005	0,046 (C)	0,005 (C)	C = 0,092 mg/m3
MAK	DEU	0,046	0,005	0,046 (C)	0,005 (C)	
VLA	ESP	0,046	0,005			
VLEP	FRA	0,09	0,01	0,18	0,02	
TLV	GRC	0,09		0,18		
RD	LTU	0,05	0,005	0,09 (C)	0,01 (C)	
TGG	NLD	0,05	5	0,19	20	
NDS/NDSch	POL	0,04				
MV	SVN	0,046	0,005	0,046	0,005	
TLV-ACGIH		0,045	0,005			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water	0,027	mg/l
Normal value in marine water	0,003	mg/l
Normal value for fresh water sediment	98,51	mg/kg
Normal value for marine water sediment	1,46	mg/kg
Normal value of STP microorganisms	10,6	mg/l
Normal value for the food chain (secondary poisoning)	NEA	
Normal value for the terrestrial compartment	19,8	mg/kg
Normal value for the atmosphere	NPI	

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation					0,045 mg/m3	NPI	0,045 mg/m3	NPI
Skin					MED	HIGH	MED	HIGH

**PHOSPHORIC ACID**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	2		4 (C)		INHAL
MAK	DEU	2		4		INHAL
VLA	ESP	1		2		
VLEP	FRA	1	0,2	2	0,5	
HTP	FIN	1		2		
TLV	GRC	1		3		
GVI/KGVI	HRV	1		2		
VLEP	ITA	1		2		
RD	LTU	1		2		
TGG	NLD	1		2		
VLE	PRT	1		2		
NDS/NDSch	POL	1		2		
TLV	ROU	1		2		
NPEL	SVK	1		2		
MV	SVN	1		2		
WEL	GBR	1		2		
OEL	EU	1		2		
TLV-ACGIH		1		3		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

## SECTION 8. Exposure controls/personal protection ... / >>

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	transparent	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	115 °C	
Flammability	not applicable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	20 °C	Method: Closed cup
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not applicable	Reason for missing data: substance/mixture reacts with water
Kinematic viscosity	1852 mm <sup>2</sup> /s	Temperature: 20 °C
Dynamic viscosity	2500 mPa*s	Temperature: 20 °C
Solubility	reacts with water developing carbon dioxide	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	not available	
Density and/or relative density	1,35 g/cm <sup>3</sup>	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Information not available

#### 9.2.2. Other safety characteristics

Total solids (250°C / 482°F) 72,30 %  
VOC (Directive 2004/42/EC) : 19,92 % - 268,98 g/litre

## SECTION 9. Physical and chemical properties ... / >>

Explosive properties	not expected
Oxidising properties	not expected

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER, ISOCYANURATE TYPE

Reacts with: water,alcohols,amines.

TOLUENE

Avoid exposure to: light.

ISOBUTYL ACETATE

Decomposes under the effect of heat.Attacks various types of plastic materials.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

ISOPHORONE DIISOCYANATE

In the air absorbs moisture.

Reacts with: water,alcohols,amines.

PHOSPHORIC ACID

Decomposes at temperatures above 200°C/392°F.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER, ISOCYANURATE TYPE

Reacts violently developing heat on contact with: amines.

On contact with: water.Develops: carbon dioxide.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

ISOBUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react violently with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances,strong acids,alkaline metals.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

ISOPHORONE DIISOCYANATE

Reacts violently developing heat on contact with: amines.

On contact with: water.Develops: carbon dioxide.

PHOSPHORIC ACID

Risk of explosion on contact with: nitromethane.May react dangerously with: alkalis,sodium borohydride.

### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ISOBUTYL ACETATE

Avoid exposure to: sources of heat,naked flames.

ETHYL ACETATE

Avoid exposure to: light,sources of heat,naked flames.

### 10.5. Incompatible materials

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER, ISOCYANURATE TYPE

## SECTION 10. Stability and reactivity ... / >>

Incompatible with: water, alcohols, amines.

POLYOXYPROPYLENEDIAMINE

Incompatible with: acids.

ISOBUTYL ACETATE

Incompatible with: strong oxidants, nitrates, strong acids, strong bases.

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, chlorosulphuric acid.

ISOPHORONE DIISOCYANATE

Avoid contact with: water, alcohols, amines, alkalis, strong oxidising agents, acids.

PHOSPHORIC ACID

Incompatible with: metals, strong alkalis, aldehydes, organic sulphides, peroxides.

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE HOMOPOLYMER, ISOCYANURATE TYPE

In decomposition develops: nitric oxide, carbon oxides.

POLYOXYPROPYLENEDIAMINE

In decomposition develops: ammonia, carbon oxides.

ISOPHORONE DIISOCYANATE

In decomposition develops: nitric oxide, carbon oxides.

PHOSPHORIC ACID

May develop: phosphoryl oxides.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies.

Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Interactive effects

## SECTION 11. Toxicological information ... / >>

### XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

### TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

### ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	Acute Tox. 4
ATE (Inhalation - vapours) of the mixture:	18,33 mg/l
ATE (Inhalation - gas) of the mixture:	Acute Tox. 4
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

### POLYOXYPROPYLENEDIAMINE

LD50 (Dermal):	2980 mg/kg OECD Guideline 402, Rabbit
LD50 (Oral):	2885 mg/kg OECD Guideline 401, Rat
LC50 (Inhalation vapours):	> 0,74 mg/l/4h OECD Guideline 403, Rat

### XYLENE (MIXTURE OF ISOMERS)

LD50 (Dermal):	4350 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	3523 mg/kg Rat
LC50 (Inhalation vapours):	26 mg/l/4h Rat
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

### BENZALDEHYDE

LD50 (Dermal):	> 2000 mg/kg Rabbit
LD50 (Oral):	1430 mg/kg Rat
LC50 (Inhalation mists/powders):	3 mg/l/4h

### AROMATIC POLYISOCYANIC PREPOLYMER

LD50 (Oral):	> 2000 mg/kg Ratto
LC50 (Inhalation mists/powders):	> 3,82 mg/l/4h

### TOLUENE

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

### 2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat

### ISOPHORONE DIISOCYANATE

LD50 (Dermal):	> 7000 mg/kg OECD Guideline 402, Rat - Wistar
LD50 (Oral):	> 4000 mg/kg OECD Guideline 401, Rat - Wistar
LC50 (Inhalation vapours):	0,04 mg/l/4h OECD Guideline 403, Rat - Wistar

### PHOSPHORIC ACID

LD50 (Dermal):	2740 mg/kg Rabbit
LD50 (Oral):	1530 mg/kg Rat
LC50 (Inhalation mists/powders):	> 0,85 mg/l/1h Rat

### SKIN CORROSION / IRRITATION

Corrosive for the skin



## SECTION 11. Toxicological information ... / >>

POLYOXYPROPYLENEDIAMINE  
OECD Guideline 404

### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

May cause respiratory irritation

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

QUARTZ

The substance has this effect only by inhalation. If it is suspended in a liquid matrix the effect does not occur.

### Route of exposure

QUARTZ  
Inhalation

### ASPIRATION HAZARD

Toxic for aspiration

## 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

POLYOXYPROPYLENEDIAMINE

LC50 - for Fish

EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants

> 15 mg/l/96h OECD Guideline 203, *Oncorhynchus mykiss*

80 mg/l/48h OECD Guideline 202, *Daphnia magna*

15 mg/l/72h OECD Guideline 201, *Pseudokirchneriella subcapitata*

**SECTION 12. Ecological information** ... / >>

BENZALDEHYDE	
LC50 - for Fish	12,4 mg/l/96h
EC50 - for Crustacea	50 mg/l/48h
Chronic NOEC for Fish	1,8 mg/l
HYDROCARBONS, C9, AROMATICS	
LC50 - for Fish	9,2 mg/l/96h OECD Guideline 203, Oncorhynchus mykiss
EC50 - for Crustacea	3,2 mg/l/48h OECD Guideline 202, Daphnia magna
EC50 - for Algae / Aquatic Plants	2,6 mg/l/72h OECD Guideline 201, Pseudokirchneriella subcapitata
TOLUENE	
LC50 - for Fish	5,5 mg/l/96h
EC50 - for Crustacea	3,78 mg/l/48h
EC50 - for Algae / Aquatic Plants	134 mg/l/72h
ISOPHORONE DIISOCYANATE	
LC50 - for Fish	> 208 mg/l/96h EU Method C.1, Cyprinus carpio
EC50 - for Crustacea	27 mg/l/48h EU Method C.2, Daphnia magna
EC50 - for Algae / Aquatic Plants	> 70 mg/l/72h EU Method C.3, Desmodesmus subspicatus

**12.2. Persistence and degradability**

BENZALDEHYDE	
Solubility in water	6950 mg/l
AROMATIC POLYISOCYANIC PREPOLYMER	
NOT rapidly degradable	
PHOSPHORIC ACID	
Solubility in water	> 850000 mg/l
Degradability: information not available	
XYLENE (MIXTURE OF ISOMERS)	
Solubility in water	100 - 1000 mg/l
Rapidly degradable	
2-METHOXY-1-METHYLETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
TOLUENE	
Solubility in water	100 - 1000 mg/l
Rapidly degradable	
ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
ISOBUTYL ACETATE	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
ISOPHORONE DIISOCYANATE	
NOT rapidly degradable	

**12.3. Bioaccumulative potential**

BENZALDEHYDE	
Partition coefficient: n-octanol/water	1,4 Log Kow
XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: n-octanol/water	3,12
BCF	25,9

## SECTION 12. Ecological information ... / >>

2-METHOXY-1-METHYLETHYL ACETATE	
Partition coefficient: n-octanol/water	1,2
TOLUENE	
Partition coefficient: n-octanol/water	2,73
BCF	90
ETHYL ACETATE	
Partition coefficient: n-octanol/water	0,68
BCF	30
ISOBUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3
ISOPHORONE DIISOCYANATE	
Partition coefficient: n-octanol/water	0,99

### 12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)	
Partition coefficient: soil/water	2,73

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2924

### 14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (TOLUENE; POLYOXYPROPYLENEDIAMINE)  
IMDG: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (TOLUENE; POLYOXYPROPYLENEDIAMINE)  
IATA: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (TOLUENE; POLYOXYPROPYLENEDIAMINE)

## SECTION 14. Transport information ... / >>

### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3 (8)

IMDG: Class: 3 Label: 3 (8)

IATA: Class: 3 Label: 3 (8)



### 14.4. Packing group

ADR / RID, IMDG, IATA: II

### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 338 Special provision: -	Limited Quantities: 1 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-C	Limited Quantities: 1 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 5 L Maximum quantity: 1 L A3	Packaging instructions: 363 Packaging instructions: 352

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## SECTION 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>			
Point	3 - 40		
<u>Contained substance</u>			
Point	75		
Point	48	TOLUENE	
		REACH Reg.: 01-2119471310-51	
Point	74	DIISOCYANATES	

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

## SECTION 15. Regulatory information ... / >>

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

One - pack performance coatings.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Met. Corr. 1</b>	Substance or mixture corrosive to metals, category 1
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 1</b>	Acute toxicity, category 1
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Resp. Sens. 1</b>	Respiratory sensitization, category 1
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1B</b>	Skin sensitization, category 1B
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H290</b>	May be corrosive to metals.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H330</b>	Fatal if inhaled.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H334</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.
<b>EUH204</b>	Contains isocyanates. May produce an allergic reaction.

Use descriptor system:

<b>ERC</b>	10a	Widespread use of articles with low release (outdoor)
<b>ERC</b>	11a	Widespread use of articles with low release (indoor)
<b>ERC</b>	8a	Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor)
<b>ERC</b>	8c	Widespread use leading to inclusion into/onto article (indoor)
<b>ERC</b>	8d	Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)
<b>ERC</b>	8f	Widespread use leading to inclusion into/onto article (outdoor)
<b>LCS</b>	PW	Widespread use by professional workers

## SECTION 16. Other information ... / >>

<b>PC</b>	1	Adhesives, sealants
<b>PC</b>	14	Metal surface treatment products
<b>PC</b>	15	Non-metal-surface treatment products
<b>PC</b>	9a	Coatings and paints, thinners, paint removers
<b>PROC</b>	10	Roller application or brushing
<b>PROC</b>	11	Non industrial spraying
<b>PROC</b>	15	Use as laboratory reagent
<b>PROC</b>	19	Manual activities involving hand contact
<b>PROC</b>	9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
<b>SU</b>	19	Building and construction work

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety

## SECTION 16. Other information ... / >>

- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

### Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.